



LICHT ECO-5000 SE

MODEL	:	ECO – 5000SE
RATED FREQUENCY (HZ)	:	60
RATED VOLTAGE (V)	:	220,230,240
RATED POWER (KW)	:	5
MAXIMUM POWER (KW)	:	5.5
DC OUTPUT	:	12V 8.3A
PHASE	:	1-Phase
POWER FACTOR	:	1.0
STARTING SYSTEM	:	Electric
BATTERY TYPE	:	12V 30AH
INSULATION GRADE	:	F
ALTERNATOR	:	SELF-EXCIATION, BRUSH
ENGINE MODEL	:	186F
ENGINE TYPE	:	1-cylinder, 4 Stroke, air cooled,
BORE X STROKE (MM)	:	86x72
DISPLACEMENT (CC)	:	418
COMPRESSION RATIO	:	19.5:1
RATED SPEED (RPM)	:	3600
FUEL TANK CAPACITY (L)	:	20
FUEL TYPE	:	DIESEL
LUBE OIL CAPACITY	:	1.65
LUBE TYPE	:	10W-30(CD grade or 15W-40)
LOW OIL PRESSURE ALARM	:	WITH
WHEELS	:	WITH
OPTIONAL	:	ATS; REMOTE CONTROL; DIGITAL PANEL
NOISE LEVEL @7M DB (A)	:	72
PACKING SIZE (LxWxH)	:	950x540x710
GROSS WEIGHT (KG)	:	155