

## KT-15000SE SPECIFICATIONS 10KVA

### GENERAL

Model	KT-15000SE
Power Factor (Cosφ)	1.0
Standby Power (Kw/Kva)	11 / 11
Prime Power (Kw/Kva)	10 / 10

### STANDARD FEATURES

- ▲ Easy operation and maintenance
- ▲ Compliance with international electrical safety standards of electrical system
- ▲ High-performance maintenance-free batteries with isolation switch
- ▲ Top lifting, forklift bottom hole design easy to transport

### ENGINE

Engine Make and Model	CD2V92
Engine Type	Air-cooled, in line, 4 stroke, 1800rpm
Fuel Type	Diesel Oil
Aspiration	Natural
Engine Prime Power (Kw)	15
Engine Standby Power (Kw)	16
Displacement ( cc )	997
Governor type	Mechanical
Starting System	Electric Start (12V)
Lubricating System	Forced Feed
Speed Regulation	±5%
Lubrication Oil capacity ( L ) Fuel	3
Operating Hour	8 to 9 hours
Battery (Ah)	45

### ALTERNATOR

Frequency (Hz) & Voltage	60HZ & 230V
Rated Power (Kw/Kva)	10 / 10
Standby Power (Kw/Kva)	11 / 11
Power Factor (Cosφ) No.	1.0
of Phases	1 phase, 2 wire
Current (A)	43.5
Type	4 pole, Rotating Field
Exciter Type	Brushless, self excited
Regulator Type	AVR
Insulation	H Class
Winding Pitch	2/3
Protection Class	IP 23
Altitude ( m )	≤1000
Voltage regulation	±1%

### OTHER INFORMATION

Type	Dimensions (LxWxH) (mm)	Dry Weight (kg)	Fuel Tank Capacity (L)	Noise Level (dB)
Open	1120x710x1030	250	25	-
Silent	1120x710x1030	270	25	77

Specifications are subject to change without notice